Product data sheet Characteristics

AP6120A

Rack PDU, Basic, 0U/1U, 100-240V/20A, 220-240V/16A, (7) C13, (2) C19





Overview

Lead time Usually in Stock



General

| Provided equipment | Installation guide Safety guide | |
|--------------------|------------------------------------|--|
| | | |
| Physical | | |

| Maximum Depth | 3.66 in (9.3 cm) | |
|----------------|-----------------------|--|
| Maximum Height | 1.73 in (4.4 cm) | |
| Net Weight | 3.44 lb(US) (1.56 kg) | |
| Maximum Width | 15.28 in (38.8 cm) | |
| | | |

Input

| Line Rated Current | 16 A |
|--------------------------|----------------------------------------------------|
| Acceptable Input Voltage | 100240 V |
| Max line current | 20 A |
| Input current limits | 20 A |
| Load Capacity | 2300 VA |
| Input Frequency | 50/60 Hz |
| Plug standard | IEC 60320 C20 |
| Nominal Input Voltage | 100 V 120 V 200 V 208 V 230 V 240 V |

Output

| Number of power socket outlets | 7 IEC 60320 C13 2 IEC 60320 C19 |
|--------------------------------|------------------------------------|
| | |

Conformance

| Product certifications | CUL Listed CE EAC IRAM PSE UL Listed |
|------------------------|-----------------------------------------------------|
| | VDE |

Ordering and shipping details

| GTIN | 00731304327851 |
|---------------------|-----------------------|
| Package weight(Lbs) | 4.45 lb(US) (2.02 kg) |

Packing Units

| 3 | | |
|------------------------------|--------------------|--|
| Package 1 Height | 8.27 in (21 cm) | |
| Package 1 width | 17.17 in (43.6 cm) | |
| Package 1 Length | 2.99 in (7.6 cm) | |
| SCC14 | 50731304327856 | |
| Number of Units in Package 3 | 100 | |
| | | |

Offer Sustainability

| oner edetainability | | |
|----------------------------|---------------------------------|--|
| Sustainable offer status | Green Premium product | |
| REACh free of SVHC | Yes | |
| EU RoHS Directive | Compliant E EU RoHS Declaration | |
| Toxic heavy metal free | Yes | |
| Mercury free | Yes | |
| RoHS exemption information | €Yes | |
| | | |

Contractual warranty

| Warranty | 2 years repair or replace |
|----------|---------------------------|
|----------|---------------------------|