

# Product data sheet

## Characteristics

# 8911DP5G53V09

Starter, Definite Purpose, nonreversing, 50A,  
3 pole, 3 phase, 208 to 240 VAC coil, melting  
alloy overload, NEMA 1



## Main

Product	Definite Purpose Starter
Ampere Rating	50 A
Horsepower Rating	3 Hp 115 V AC, 1 phase 10 Hp 230 V AC, 1 phase 15 Hp 230 V AC, 3 phase 30 Hp 460 V AC, 3 phase 30 hp 575 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Circuit Voltage	220 V AC 50 Hz 208...240 V AC 60 Hz
Phase	3 phase

## Complementary

Enclosure Material	Painted sheet steel
Enclosure Rating	NEMA 1
Locked Rotor Amperes	300 A 230 V AC 250 A 460 V AC 200 A 575 V AC
Number of Poles	3P
Range	DPS
Overload Type	Melting alloy
Number of Thermal Units	3

## Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901025108
Nbr. of units in pkg.	1
Package weight(Lbs)	9.5 lb(US) (4.31 kg)
Returnability	Yes
Country of origin	CN

## Packing Units

Package 1 Height	7.20 in (18.288 cm)
Package 1 width	7.50 in (19.050 cm)
Package 1 Length	20.50 in (52.070 cm)

## Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

## Contractual warranty

Warranty	18 months
----------	-----------