



Main

Range	Spacial
Product name	Spacial S3XEX
Enclosure type	ATEX certified application
Category	Compact enclosure
Nominal height	11.81 in (300 mm)
Nominal width	7.87 in (200 mm)
Nominal depth	5.91 in (150 mm)
Product installation	Wall-mounting
Product destination	For potentially explosive atmosphere
Device composition	1 body 1 lock door 1 door 2 perforated vertical profile drilled door

Complementary

Body type	Single piece body, cross-shaped structure Gutter shaped front rail
Door type	Solid
Number of doors	Front face 1
Door opening side	Reversible 120 °)
Lock type	3 mm double-bar lock
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Accessibility for operation	Front
Removable parts	Door by hinges
Material	Body and door stainless steel 304L Lock zamak Hinge stainless steel
Surface finish	Body and door Scotch-Brite® brushed Lock chromium plated
Net Weight	6.97 lb(US) (3.16 kg)

Environment

Standards	EN 60079-0 : 2004 EN 61241-1 : 2004 EN 61241-0 : 2005 EN 60079-7 : 2006
Product certifications	LOM 09ATEX3068U
IP degree of protection	IP66 IEC 60529 according to the ATEX directive 94/9/EC)
IK degree of protection	IK10 IEC 62262

Ordering and shipping details

Category	80034 - ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	03606480155352
Nbr. of units in pkg.	1
Package weight(Lbs)	6.95 lb(US) (3.15 kg)
Returnability	No
Country of origin	BG

Packing Units

Package 1 Height	8.27 in (210.000 mm)
Package 1 width	12.20 in (310.000 mm)
Package 1 Length	7.09 in (180.000 mm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------