



## Main

|                               |                                                    |
|-------------------------------|----------------------------------------------------|
| Range of product              | Hyde Park                                          |
| Sensor type                   | Ultrasonic sensor                                  |
| Series name                   | Superprox 900                                      |
| Device short name             | SM900                                              |
| Sensor design                 | Cylindrical M30                                    |
| [Sn] nominal sensing distance | 3.28 ft (1 m)                                      |
| Type of sensing window        | Adjustable                                         |
| Material                      | Stainless steel                                    |
| Enclosure material            | Stainless steel 303                                |
| Front material                | Silicone rubber                                    |
| Type of output signal         | Discrete                                           |
| Discrete output function      | 1 NO                                               |
| ISO thread                    | M30 x 1.5                                          |
| Wiring technique              | 4-wire                                             |
| [Us] rated supply voltage     | 12...24 V DC overload and short-circuit protection |
| Supply voltage limits         | 10...28 V DC                                       |
| Discrete output type          | PNP/NPN                                            |
| Electrical connection         | Cable, 9.84 ft (3 m)                               |
| Product specific application  | -                                                  |

## Complementary

|                                       |                                                          |
|---------------------------------------|----------------------------------------------------------|
| [Sd] sensing range                    | 0.17...3.28 ft (0.0508...1 m)                            |
| [Sa] assured operating distance       | 0.17...3.28 ft (0.0508...1 m) teach push-button          |
| Maximum differential travel           | 0.10 in (2.5 mm)                                         |
| Blind zone                            | 0.00...2.01 in (0...51 mm)                               |
| Transmission frequency                | 200 kHz                                                  |
| Repeat accuracy                       | 0.87 %                                                   |
| Minimum size of detected object       | Cylinder diameter 1.6 mm - up to 305 mm sensing distance |
| Current consumption                   | 100 mA                                                   |
| Maximum switching current             | 100 mA reverse polarity protection                       |
| Resistance to electrostatic discharge | 8 kV level 4 IEC 61000-4-2                               |
| Maximum Height                        | 1.18 in (30 mm)                                          |
| Maximum Width                         | 1.37 in (34.7 mm)                                        |
| Maximum Depth                         | 1.18 in (30 mm)                                          |
| Length                                | 3.74 in (95 mm)                                          |
| Net Weight                            | 2.09 lb(US) (0.95 kg)                                    |

## Environment

|                                       |                           |
|---------------------------------------|---------------------------|
| Product certifications                | UL                        |
| Marking                               | CE                        |
| NEMA degree of protection             | NEMA 4X indoor use only)  |
| IP degree of protection               | IP67                      |
| Ambient air temperature for operation | 32...122 °F (0...50 °C)   |
| Ambient air temperature for storage   | -4...176 °F (-20...80 °C) |

|                                      |                                          |
|--------------------------------------|------------------------------------------|
| Relative humidity                    | 100 % without condensation               |
| Vibration resistance                 | +/-1 mm 10...55 Hz)IEC 60068-2-6         |
| Shock resistance                     | 30 gn in all 3 axes 11 ms IEC 60068-2-27 |
| Resistance to electromagnetic fields | 9.14 V/m (10 V/m) level 3 IEC 61000-4-3  |
| Resistance to fast transients        | 1 kV level 3 IEC 61000-4-4               |

## Ordering and shipping details

|                     |                                    |
|---------------------|------------------------------------|
| Category            | 22490 - SENSORS-ULTRASONIC (XX5,6) |
| Discount Schedule   | DS2                                |
| GTIN                | 03389119112116                     |
| Package weight(Lbs) | 0.86 lb(US) (0.39 kg)              |
| Returnability       | No                                 |
| Country of origin   | US                                 |

## Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                                              |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                                                                        |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                                            |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>                                                                                                                                                                                                               |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                                          |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                                                                          |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                                                                                |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                                                                                                                                                                                                                                      |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|