

Main

Product or component type	Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	45 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	10 HP 200 V AC 15 HP 230 V AC 25 HP 460 V AC 25 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	2 momentary push-buttons (START-STOP) and selector switch (HAND-OFF-AUTO)
Auxiliary Contacts	1 NO + 1 NC
Thermal overload type	Melting alloy 3
Electrical connection	Screw clamp terminals
NEMA size	2



Environment

Enclosure Type	NEMA 1 painted sheet steel
Product certifications	NEMA CSA UL Listed

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
Package weight(Lbs)	20 lb(US) (9.07 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------