



### Main

|                           |                                           |
|---------------------------|-------------------------------------------|
| Range of product          | Harmony 9001SK                            |
| Product or component type | Non-illuminated mushroom head push-button |
| Device short name         | 9001SK                                    |
| Bezel material            | Black plastic                             |

### Complementary

|                              |                            |
|------------------------------|----------------------------|
| Mounting diameter            | 1.18 in (30 mm)            |
| CAD overall width            | 1.81 in (46 mm)            |
| CAD overall height           | 1.77 in (45 mm)            |
| CAD overall depth            | 2.72 in (69 mm)            |
| Net Weight                   | 0.21 lb(US) (0.095 kg)     |
| Operating position           | Any position               |
| Shape of signaling unit head | Round                      |
| Type of operator             | maintained                 |
| Operator profile             | Mushroom Ø 41 mm, unmarked |
| Mechanical durability        | 5000000 cycles             |

### Environment

|                                       |                                                                                                                                  |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Protective treatment                  | TC                                                                                                                               |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)                                                                                                       |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C)                                                                                                       |
| Electrical shock protection class     | Class II IEC 61140                                                                                                               |
| IP degree of protection               | IP66 IEC 60529                                                                                                                   |
| NEMA degree of protection             | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 4X                                                 |
| Standards                             | CSA C22.2 No 14<br>EN/IEC 60947-5-1<br>EN/IEC 60947-1<br>EN/IEC 60947-5-4<br>JIS C 4520<br>JIS C 852<br>UL 508<br>RoHS compliant |
| Product certifications                | UL 508<br>UL listed file E78403 CCN NKCR<br>NEMA<br>CSA LR25490 class 3211 03                                                    |
| Vibration resistance                  | 7 gn 2...500 Hz)IEC 60068-2-6                                                                                                    |
| Shock resistance                      | 50 gn IEC 60068-2-27                                                                                                             |

## Ordering and shipping details

|                       |                      |
|-----------------------|----------------------|
| Category              | 21429 - 9001 SK,SKY  |
| Discount Schedule     | CS1                  |
| Nbr. of units in pkg. | 1                    |
| Package weight(Lbs)   | 0.5 lb(US) (0.23 kg) |
| Returnability         | No                   |
| Country of origin     | MX                   |

## Packing Units

|                  |                      |
|------------------|----------------------|
| Package 1 Height | 5.08 in (12.903 cm)  |
| Package 1 width  | 2.00 in (5.080 cm)   |
| Package 1 Length | 12.90 in (32.774 cm) |

## Offer Sustainability

|                            |                                                                                                                              |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                        |
| REACH free of SVHC         | Yes                                                                                                                          |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>                               |
| Toxic heavy metal free     | Yes                                                                                                                          |
| Mercury free               | Yes                                                                                                                          |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                          |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                       |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|