9080PF1

Linergy terminal block, fuse holder, Class H or K, 30 A, 250 V, 1 pole



Main	
Range	9080FB
Product	Fuse holder

Complementary

Complementary	
Current Rating	30 A
[Ue] rated operational voltage	<= 250 V AC/DC
Fuse type	H and K
Fuse size	0.5625 x 2 in
Number of poles	1
Electrical connection	Pressure wire clamp
Wire Gauge	AWG 18AWG 10 copper or aluminium
SCCR	10 kA UL 512
Product certifications	CE UL listed file E40747 CCN IZLT CSA file 70360 class 6225 01
Operating Temperature	-40257 °F (-40125 °C)
Mounting Type	Surface mount
Block Material	Thermoplastic block
Wire stripping length	0.4375 in (11.11 mm)
Terminal Tightening Torque	Screw terminals 2.82 N.m (25 lbf.in) AWG 14AWG 10 copper
Maximum Height	3 in (76.20 mm)
Maximum Width	28.45 mm (1.12 in)
Maximum Depth	1.38 in (35.05 mm)

Ordering and shipping details

Category	21704 - 9080 K (BLOCKS ONLY)
Discount Schedule	CP1
GTIN	00785901567004
Package weight(Lbs)	0.18 lb(US) (0.08 kg)
Returnability	Yes
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	d China RoHS Declaration

Warranty 18 months