



### Main

|                           |                                |
|---------------------------|--------------------------------|
| Product or component type | Industrial Control Transformer |
| Power Rating              | 1000 VA<br>1500 VA             |
| Primary Voltage           | 415 V                          |
| Secondary Voltage         | 110 V                          |
| Type                      | T                              |

### Complementary

|                                |   |
|--------------------------------|---|
| Number of Phases               | 1 phase   |
| Power Rating                   | 1500 VA UL<br>1500 VA CSA<br>1500 VA NOM<br>1000 VA |
| Primary to Secondary Voltage   | 415 V 110 V   |
| Temperature rise               | 115 °C  |
| Electrical connection          | Screw clamp terminals                               |
| Fingersafe Cover Compatibility | FSC2  |

### Environment

|                        |                         |
|------------------------|-------------------------|
| Product certifications | UL Listed<br>CSA        |
| Enclosure Type         | Not rated (open device) |
| Insulation temperature | 356 °F (180 °C)         |

### Ordering and shipping details

|                       |                                    |
|-----------------------|------------------------------------|
| Category              | 16201 - 9070 T (NOT TF) 250-2000VA |
| Discount Schedule     | CP8                                |
| Nbr. of units in pkg. | 1                                  |
| Package weight(Lbs)   | 33.6 lb(US) (15.24 kg)             |
| Returnability         | No                                 |
| Country of origin     | US                                 |

### Packing Units

|                  |                      |
|------------------|----------------------|
| Package 1 Height | 11.00 in (27.940 cm) |
| Package 1 width  | 11.25 in (28.575 cm) |
| Package 1 Length | 14.19 in (36.043 cm) |

Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product                         |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>                           |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |
| PVC free                   | Yes   |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

## Connections and Wiring Diagrams

### Voltage and Connection Options

| Voltage Code | Voltages  |                       | Connections   |   |
|--------------|-----------|-----------------------|---|---|
|              | Primary   | Secondary             | Primary   | Secondary   |
| D15          | 240 x 480 | 23/110<br>24/<br>/120 | 240: Connect to H1 and H4<br>Jumper H1 with H3<br>Jumper H2 with H4<br>480: Connect to H1 and H4<br>Jumper H2 with H3 | 23 or 24 or 25:<br>Connect to X1 and X2<br>110 or 115 or 120:<br>Connect to X1 and X3 |

