9001SKP38R31 PILOT LIGHT 120V 30MM SK +OPTIONS





Main

Lens type	Fresnel plastic
Light block supply	Full voltage 120 V

Complementary

Bezel material	Plastic	
Mounting diameter	1.18 in (30 mm)	
Shape of signaling unit head	Round	
Operating mode	Normal	

Environment

Protective treatment	TC
IP degree of protection	IP66

Ordering and shipping details

Category	21429 - 9001 SK,SKY	
Discount Schedule	CS1	
GTIN	00785901041573	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.18 lb(US) (0.08 kg)	
Returnability	Yes	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	1.90 in (4.826 cm)	
Package 1 width	2.30 in (5.842 cm)	
Package 1 Length	3.70 in (9.398 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫ _{Yes}	
China RoHS Regulation	☑ China RoHS Declaration	

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Contractual warranty	
Warranty	18 months