Product data sheet Characteristics

9001K2L38LRR21H13 PUSH BUTTON 600VAC 10A 30MM T-K





Main

Range of product	Harmony 9001K
Product or component type	Illuminated push-button
Device short name	К
Operator additional information	Full guard in plastic

Complementary

Bezel material	Chromium plated metal	
Mounting diameter	1.18 in (30 mm)	
Light block supply	Full voltage	
[le] rated operational current	10 A, AC-15 10 A, DC-13	
Contact operation	Standard	
Device presentation	Complete product	

Environment

Product certifications	NEMA CSA LR 25490 class 3211 03 UL listed file E42259 CCN NKCR CE
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13

Ordering and shipping details

Cracing and cripping actanc		
Category	21426 - 9001 K (NOT KA,KM,KX)	
Discount Schedule	CS1	
GTIN	00785901636021	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.5 lb(US) (0.23 kg)	
Returnability	No	
Country of origin	MX	

Packing Units

Package 1 Height	11.43 in (29.032 cm)	
Package 1 width	4.50 in (11.430 cm)	
Package 1 Length	29.03 in (73.742 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEN RoHS
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	☑ Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months