



Main

Product or component type	Plug-in unit
Range of product	I-Line
Circuit breaker type	J-frame
Trip unit technology	Electronic, standard, Micrologic 3.2 S, LSI

Complementary

Protection type	Circuit breaker
Mounting mode	Plug-in
[Ue] rated operational voltage	600 V AC
Line Rated Current	250 A
Number of Phases	3 phase
Poles description	3P
Interrupt Rating	125 KA 240 V AC 100 KA 480 V AC 50 kA 600 V AC
[Ics] rated service short-circuit breaking capacity	80 %
Wiring configuration	4-wire (integral ground bus)
AWG gauge	AWG 6...AWG 2/0 1 ground AWG 3/0...350 kcmil 1 phase and neutral
Maximum Depth	9.13 in (232 mm)
Maximum Height	8.50 in (216 mm)
Maximum Width	21.69 in (551 mm)

Environment

Product certifications	CSA C22.2 No 27 UL listed file E22182
Standards	UL 857 IEC 60529
IP degree of protection	IP54

Ordering and shipping details

Category	20185-PJD C/B PLUGS
Discount Schedule	PE7
Package weight(Lbs)	32.00 lb(US) (14.515 kg)
Returnability	No

Contractual warranty

Warranty	18 months
----------	-----------