# VW3S8208R15

# cable for pulse/direction signal - 5 V - 1.5 m





#### Main

Accessory / separate part designation	Cable for pulse/direction signal
Accessory / separate part type	Connecting cable
Accessory / separate part category	Connection accessories
Accessory / separate part destination	Between stepper drive SD326 and motion controller TLM2
Range compatibility	Lexium SD3
Cable length	4.92 ft (1.5 m)

## Complementary

Product compatibility	SD326	
[Uc] control circuit voltage	5 V	
Electrical connection	1 connector 24-pole Molex SD326) 1 connector SUB-D 15 TLM2)	

#### Ordering and shipping details

Category	18286 - STEPPER ACCESSORIES
Discount Schedule	PC55
GTIN	03389119224697
Nbr. of units in pkg.	1
Package weight(Lbs)	2.2 lb(US) (1.00 kg)
Returnability	No
Country of origin	DE

#### **Packing Units**

Package 1 Height	0.300 dm	
Package 1 width	4.000 dm	
Package 1 Length	3.000 dm	

### Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	<b>⊡</b> End Of Life Information	

Warranty 18 months