



### Main

Range	9422T
Product	Disconnect Switch
Disconnect Type	Non-fusible disconnect switch

### Complementary

Mounting Type	Flange rod variable depth
Current Rating	100 A
Horsepower Rating	25 Hp 200 V AC 30 Hp 230 V AC 60 Hp 460 V AC 75 Hp 575 V AC 20 hp 250 V DC
Handle Type	Ordered separately

### Environment

Certifications	UL Recognized CSA
----------------	----------------------

### Ordering and shipping details

Category	21732 - 9422
Discount Schedule	CP1
GTIN	00785901879824
Package weight(Lbs)	6.36 lb(US) (2.88 kg)
Returnability	No
Country of origin	MX

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

Contractual warranty

Warranty	18 months
----------	-----------