

Product data sheet

Characteristics

8903SZG2V04

Contactor, Type S, multipole lighting,
electrically held, 600A, 3 pole, 277 VAC 60 Hz
coil, NEMA 1

Main

Product	Electrically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	277 V AC 60 Hz
Current Rating	600 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical connection	Lugs
Maximum Depth	13.11 in (333 mm)
Maximum Width	20.20 in (513 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel surface none
Product certifications	UL Listed CSA

Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
Package weight(Lbs)	290 lb(US) (131.54 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Will be compliant – Date to be confirmed
-------------------	--

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the company. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.