



Main

| | |
|---------------------------|--|
| Product or component type | Plug-in unit |
| Range of product | I-Line |
| Circuit breaker type | J-frame |
| Trip unit technology | Electronic, ammeter, Micrologic 5.2 A, LSI |

Complementary

| | |
|---|---|
| Protection type | Circuit breaker |
| Mounting mode | Plug-in |
| [Ue] rated operational voltage | 600 V AC |
| Line Rated Current | 250 A |
| Number of Phases | 3 phase |
| Poles description | 3P |
| Interrupt Rating | 65 KA 240 V AC 35 KA 480 V AC 18 kA 600 V AC |
| [Ics] rated service short-circuit breaking capacity | 80 % |
| Wiring configuration | 4-wire (integral ground bus) |
| AWG gauge | AWG 6...AWG 2/0 1 ground AWG 3/0...350 kcmil 1 phase and neutral |
| Maximum Depth | 9.13 in (232 mm) |
| Maximum Height | 8.50 in (216 mm) |
| Maximum Width | 21.69 in (551 mm) |

Environment

| | |
|-------------------------|--|
| Product certifications | CSA C22.2 No 27 UL listed file E22182 |
| Standards | IEC 60529 UL 857 |
| IP degree of protection | IP54 |

Ordering and shipping details

| | |
|---------------------|--------------------------|
| Category | 20185-PJD C/B PLUGS |
| Discount Schedule | PE7 |
| Package weight(Lbs) | 32.00 lb(US) (14.515 kg) |
| Returnability | No |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|