



Overview

Presentation	Tall and wide enclosure with 48U spaces for additional equipment and increased cable management options for high density server and networking applications.
Lead time	Usually in Stock

General

Provided equipment	Baying hardware Key(S) Leveling feet Mounting Hardware Pre-installed casters Side Panels
--------------------	---

Physical

Maximum Mounting Depth	36.02 in (91.49 cm)
Number of rack unit	48U
Minimum Mounting Depth	10.31 in (26.19 cm)
Marking	14 gauge EIA mounting rail 16 gauge post 18 gauge roof 18 gauge side panels
Color	Black
Maximum Depth	42.13 in (107 cm)
Rack Width	19"
Maximum Height	88.90 in (225.8 cm)
Net Weight	308.05 lb(US) (139.73 kg)
Permanent permissible load	2250 Lb(US) (1020.58 kg) dynamic 3000 lb(US) (1360.78 kg) static
Maximum Width	29.53 in (75 cm)

Conformance

Standards	UL 2416 UL 60950-1 EIA-310E
-----------	-----------------------------------



Ordering and shipping details

GTIN	00731304294207
Package weight(Lbs)	341.12 lb(US) (154.73 kg)

Packing Units

Package 1 Height	94.49 in (240 cm)
Package 1 width	35.24 in (89.5 cm)
Package 1 Length	47.99 in (121.9 cm)
Number of Units in Package 3	1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------