



Main

Product	Well-Guard Control
Type	Class 8940 type SS
Device application	Pumping

Complementary

Control Circuit Type	Common control circuit
Control Circuit Voltage	240 V AC 60 Hz 220 V AC 50 Hz
Line Rated Current	90 A
Number of Poles	3
Horsepower Rating	30 hp 240 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Units	Selector switch HAND-OFF-AUTO) Push-button START)
Disconnect Type	Fusible disconnect switch
Associated fuse rating	100 A
Fuse type	H or K
Thermal overload type	Motor Logic solid state class 10/20
Protection type	Overload Phase loss Phase unbalance
Device mounting	Surface
Electrical connection	Screw terminal
NEMA size	3
Maximum Height	38.15 in (969 mm)
Maximum Width	24.57 in (624 mm)
Maximum Depth	10.39 in (264 mm)

Environment

NEMA Rating	NEMA 3R
Enclosure type	Weatherproof enclosure indoor/outdoor
Product certifications	UL Listed NEMA

Ordering and shipping details

Category	21389 - 8940 NSE,NSF
Discount Schedule	CP1
GTIN	00785901104490
Package weight(Lbs)	122 lb(US) (55.34 kg)
Returnability	Yes
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------