9001SKR3BH13 PUSHBUTTON 600VAC 10AMP 30MM SK +OPTIONS





Main	
Range of product	Harmony 9001SK
Product or component type	Push-button
Device short name	9001SK
Type of operator	Spring return
Operator profile	Black projecting
Operator additional	Without guard

\sim									
	\sim r	n	n	\sim	m	Δ	71	. ~	r\/
	UJI		U)	•		C1	-11	$\boldsymbol{\alpha}$	rv
_	•		т.	_		•			

Bezel material	Plastic	
Mounting diameter	1.18 in (30 mm)	
Contacts type and composition	1 C/O	
Contact operation	Standard	
Mechanical durability	5000000 cycles	
Device presentation	Complete product	

Environment

Standards	UL 508	
	JIS C 852	
	EN/IEC 60947-1	
	EN/IEC 60947-5-4	
	CSA C22.2 No 14	
	EN/IEC 60947-5-1	
	JIS C 4520	:
IP degree of protection	IP66	
NEMA degree of protection	NEMA 1/2/3/3R/4/4X/6/12/13	

Ordering and shipping details

<u> </u>		
Category	21429 - 9001 SK,SKY	
Discount Schedule	CS1	
GTIN	00785901042662	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.16 lb(US) (0.07 kg)	
Returnability	Yes	
Country of origin	MX	

Packing Units

Package 1 Height	5.08 in (12.903 cm)
Package 1 width	2.00 in (5.080 cm)
Package 1 Length	12.90 in (32.774 cm)

1

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

Contractual warranty

Warranty	18 months