



### Overview

Lead time Usually in Stock

### General

Provided equipment	CD with software Documentation CD Installation guide Temperature Probe USB cable Warranty card Web/SNMP Management Card
--------------------	---

### Physical

Color	Black
Maximum Depth	28.15 in (71.5 cm)
Maximum Height	17.01 in (43.2 cm)
Net Weight	245.99 lb(US) (111.58 kg)
Maximum Width	10.35 in (26.3 cm)

### Input

Input Frequency	40 - 70 Hz auto-sensing
Number of input connectors	1 Hard Wire 3-wire (2PH + G)
Efficiency at full load	100...275 V adjustable (half load) 160...275 V
Other Input Voltages	240 V
Nominal Input Voltage	208 V

### Output

Kw Rating	8000 W
Max Configurable Power (Watts)	8000 W
Harmonic distortion	Less than 2%
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
Other Output Voltages	240 V
Crest factor	3 : 1
Topology	Double Conversion Online
Waveform Type	Sine wave
Output connector type	Hard Wire 3-wire (2PH + G) 1
Nb of power socket outlets	4 NEMA L6-20R 2 NEMA L6-30R

Bypass type	Internal Bypass (Automatic and Manual)
Output voltage	208 V

## Conformance

Product certifications	ENERGY STAR V2.0 (USA) FCC part 15 class A NOM TAA compliance UL 1778
Standards	CSA C22.2 No.107.3-05

## Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	55 dBA
Online Thermal Dissipation	1712 Btu/h
IP degree of protection	IP20

## Batteries & Runtime

Battery type	Lead-Acid battery
Included Battery Modules	0
Typical recharge time	1.5 h
RBC Quantity	2
Liquid Electrolyte Value	0

## Communications & Management

Free slots	1
Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes

## Surge Protection and Filtering

Surge energy rating	480 J
---------------------	-------

## Ordering and shipping details

Package weight(Lbs)	279.00 lb(US) (126.55 kg)
---------------------	---------------------------

## Packing Units

Package 1 Height	18.15 in (46.1 cm)
Package 1 width	23.62 in (60 cm)
Package 1 Length	39.37 in (100 cm)
Number of Units in Package 3	1

## Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---