Product data sheet Characteristics

ZCKJ18H7

limit switch body ZCKJ - fixed - w/o display - 1NC+1NO - snap action - 1/2"NPT



Main	
Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch body
Device short name	ZCKJ
Body type	Fixed
Product compatibility	XCKJ
Associated head	ZCKE08 ZCKE619 ZCKE61 ZCKE62 ZCKE05 ZCKE66 ZCKE65 ZCKE65 ZCKE64 ZCKE21 ZCKE64 ZCKE23 ZCKE67 ZCKE629 ZCKE63
Body material	Metal
Cable entry	1 entry tapped for 1/2" NPT conduit
Number of poles	2
Contacts type and composition	1 NC + 1 NO
Contact operation	Snap action

1 1 position

Gold plated contacts

Complementary

Complementary		
Local display	Without	
Electrical connection	Screw-clamp terminals 1 x 0.342 x 1.5 mm ²	
Positive opening	With	
Minimum actuation speed	0.01 m/min	
[le] rated operational current	3 A 240 V, AC-15, A300 EN/IEC 60947-5-1 appendix A 0.27 A 250 V, DC-13, Q300 EN/IEC 60947-5-1 appendix A	
[Ithe] conventional enclosed thermal current	10 A	
[Ui] rated insulation voltage	500 V 3)IEC 60947-1 contact block 300 VCSA C22.2 No 14 contact block 300 VUL 508 contact block	
Maximum resistance across terminals	0.25 mOhm IEC 60255-7 category 3	
[Uimp] rated impulse withstand voltage	6 KV IEC 60664 6 kV IEC 60947-1	
Short-circuit protection	10 A cartridge fuse gG	
Electrical durability	5000000 Cycles, DC-13 120 V, 4 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 10 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C	
Maximum Width	1.57 in (40 mm)	
Height	3.03 in (77 mm)	
Maximum Depth	1.73 in (44 mm)	

Number of steps

Contacts material

Net Weight	0.68 lb(US) (0.31 kg)	
Terminals description ISO n°1	(23-24)NO (11-12)NC	
	(13-14)NO	
	(21-22)NC	
Environment		
IP degree of protection	IP66	
IK degree of protection	IK07	
Ambient air temperature for operation	-13158 °F (-2570 °C) standard environment	
	50248 °F (10120 °C) high temperature	
	-40158 °F (-4070 °C) low temperature	
Ambient air temperature for storage	-40248 °F (-40120 °C)	
Environmental characteristic	High temperature	
	Standard environment	
Ordering and shipping details	Low temperature	
Ordering and shipping details Category	22411-LIMIT SWITCHES,IEC,XCKJ	
	·	
Category	22411-LIMIT SWITCHES,IEC,XCKJ	
Category Discount Schedule	22411-LIMIT SWITCHES,IEC,XCKJ	
Category Discount Schedule GTIN	22411-LIMIT SWITCHES,IEC,XCKJ T 03389118130401	
Category Discount Schedule GTIN Package weight(Lbs)	22411-LIMIT SWITCHES,IEC,XCKJ T 03389118130401 10.24 oz (290.299 g)	
Category Discount Schedule GTIN Package weight(Lbs) Returnability Country of origin	22411-LIMIT SWITCHES,IEC,XCKJ T 03389118130401 10.24 oz (290.299 g) No	
Category Discount Schedule GTIN Package weight(Lbs) Returnability Country of origin	22411-LIMIT SWITCHES,IEC,XCKJ T 03389118130401 10.24 oz (290.299 g) No	
Category Discount Schedule GTIN Package weight(Lbs) Returnability Country of origin Offer Sustainability	22411-LIMIT SWITCHES,IEC,XCKJ T 03389118130401 10.24 oz (290.299 g) No FR WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go	
Category Discount Schedule GTIN Package weight(Lbs) Returnability Country of origin Offer Sustainability California proposition 65	22411-LIMIT SWITCHES,IEC,XCKJ T 03389118130401 10.24 oz (290.299 g) No FR WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov	

Contractual	warrantv
Contractadi	warranty

•		
Warranty	18 months	