ZB5AG6R26

selector switch head Ø22 2-position spring return Ronis 455 blue key switch



Main

| Range of product | Preventa XY2C |
|-------------------------------|------------------------------|
| Product or component type | Head for key selector switch |
| Device short name | ZB5 |
| Bezel material | Plastic |
| Mounting diameter | 0.87 in (22 mm) |
| Sale per indivisible quantity | 1 |
| Shape of signaling unit head | Round |
| Type of operator | Right to left spring return |
| Operator profile | Blue key switch |
| Operator position information | 2 positions 90° |
| Type of keylock | Ronis 455 |
| Key withdrawal position | Left |

Complementary

| CAD overall width | 1.14 in (29 mm) |
|-----------------------------|--|
| CAD overall height | 1.14 in (29 mm) |
| CAD overall depth | 2.83 in (72 mm) |
| Net Weight | 0.13 lb(US) (0.061 kg) |
| Mechanical durability | 1000000 cycles |
| Station name | XALD 15 cut-outs XALK 25 cut-outs |
| Electrical composition code | C4 6 single and double front mounting C5 5 single front mounting C6 5 single and double front mounting C7 4 single front mounting C8 4 single and double front mounting C11 3 single front mounting C3 6 single front mounting SF1 3 single front mounting SR1 3 single front mounting C15 1 single front mounting |

Environment

| Ziivii Giiiii Gii | |
|---------------------------------------|---|
| Protective treatment | TH |
| Ambient air temperature for storage | -40158 °F (-4070 °C) |
| Ambient air temperature for operation | -13158 °F (-2570 °C) |
| Electrical shock protection class | Class II IEC 60536 |
| IP degree of protection | IP69K IEC 60529 |
| NEMA degree of protection | NEMA 13 NEMA 4X |
| Resistance to high pressure washer | 1015.26 psi (7000000 Pa) 131 °F (55 °C) 0.1 m |
| IK degree of protection | IK06 IEC 50102 |
| Standards | EN/IEC 60947-1 EN/IEC 60947-5-4 JIS C 4520 CSA C22.2 No 14 EN/IEC 60947-5-1 UL 508 |

| Product certifications | UL Listed |
|---|--|
| | DNV |
| | LROS (Lloyds register of shipping) RINA |
| | CSA |
| | BV |
| | GL |
| Vibration resistance | 5 gn 2500 Hz)IEC 60068-2-6 |
| Shock resistance | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 |
| | 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27 |
| . | |
| Ordering and shipping details Category | 22467 - PUSHBUTTONS,22MM(PLASTIC) NEW |
| Discount Schedule | CS2 |
| GTIN | 03389119061674 |
| | |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.1 lb(US) (0.05 kg) |
| Returnability | No |
| Country of origin | FR |
| Packing Units | |
| Package 1 Height | 0.860 dm |
| Package 1 width | 0.330 dm |
| Package 1 Length | 0.520 dm |
| | |
| Offer Sustainability | |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State or California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov |
| | |

18 months

Contractual warranty

Warranty