

# Product data sheet

## Characteristics

# 8903SQG61V02C

Contactor, Type S, combination lighting,  
electrically held, 3 pole, 100A, 600 V fuse,  
110/120 VAC 50/60 Hz coil, NEMA 1



## Main

Product	Combination electrically held lighting contactor
Type	S

## Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	100 A
Number of Poles	3P
Control Units	Selector switch 3 positions HAND-OFF-AUTO)
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Disconnecter device type	Fusible disconnect switch R, 100 A 600 V
Electrical connection	Lugs
Maximum Height	39.49 in (1003 mm)
Maximum Depth	10.59 in (269 mm)
Maximum Width	15.24 in (387 mm)

## Environment

Enclosure Type	NEMA 1 painted sheet steel surface none
Product certifications	UL listed file E16151 CCN NRNT

## Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
Package weight(Lbs)	113 lb(US) (51.26 kg)
Returnability	No
Country of origin	MX

## Offer Sustainability

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------