



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	Casters Doors Ground studs Installation guide Leveling feet Mounting Hardware Roof Side Panels
--------------------	---------------------------------------------------------------------------------------------------------------------

Physical

Maximum Mounting Depth	35.79 in (90.91 cm)
Net Depth with Stabilizing Feet	42.13 in (1070.10 mm)
Number of rack unit	42U
Minimum mounting depth	7.40 in (18.8 cm)
Marking	14 gauge EIA mounting rail 16 gauge front door 14 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels
Color	Black
Maximum Depth	42.13 in (107 cm)
Rack Width	19"
Height	78.39 in (199.1 cm)
Net weight	275.78 lb(US) (125.09 kg)
Permanent permissible load	2250 Lb(US) (1020.58 kg) dynamic 3750 lb(US) (1700.97 kg) static
Width	23.62 in (60 cm)

Conformance

Standards	EIA-310D
-----------	----------



Ordering and shipping details

GTIN	00731304241553
Package weight(Lbs)	318.68 lb(US) (144.55 kg)

Packing Units

Package 1 Height	83.39 in (211.8 cm)
Package 1 width	35.39 in (89.9 cm)
Package 1 Length	47.99 in (121.9 cm)
Number of Units in Package 3	1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------