9001KR8Y PUSHBUTTON OPERATOR 30MM TYPE K +OPTIONS





<i>f</i> lain	
Range of product	Harmony 9001K
Product or component type	Mushroom head push-button
Device short name	9001K
Type of operator	push-pull
Operator profile	Yellow mushroom Ø 41 mm, unmarked

Com	plemen	tary

o o in promortion y		
Bezel material	Chromium plated metal	
Mounting diameter	1.18 in (30 mm)	
Net Weight	0.43 lb(US) (0.195 kg)	
Operating position	Any position	
Shape of signaling unit head	Round	
Head material	Plastic	
Operator position information	3 positions	
Contacts type and composition	Without contact block	
Mechanical durability	5000000 cycles	
Device presentation	Basic element	

Environment

Environment		
Protective treatment	TC	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
Overvoltage category	Class II IEC 61140	
IP degree of protection	IP66 IEC 60529	
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4 NEMA 6	
Standards	EN/IEC 60947-5-1 EN/IEC 60947-1 EN/IEC 60947-5-4 JIS C 4520 JIS C 852 UL 508 CSA C22.2 No 14	
Product certifications	UL 508 NEMA	
Vibration resistance	7 gn 2500 Hz)IEC 60068-2-6	
Shock resistance	50 gn IEC 60068-2-27	

Ordering and shipping details

Category	21426 - 9001 K (NOT KA,KM,KX)	
Discount Schedule	CS1	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.5 lb(US) (0.23 kg)	
Returnability	No	
Country of origin	MX	

Packing Units

Package 1 Height	11.43 in (29.032 cm)
Package 1 width	4.50 in (11.430 cm)
Package 1 Length	29.03 in (73.742 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

	, or it dotted that tall to		
Warranty	18 months		