



Main

Product or component type	Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	18 A
Number of Poles	4P
Number of Phases	2 phases
Horsepower Rating	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Thermal overload type	Melting alloy 2
Electrical connection	Screw clamp terminals
NEMA size	0
Maximum Height	6.77 in (172 mm)
Maximum Depth	4.21 in (107 mm)
Maximum Width	4.53 in (115 mm)

Environment

Enclosure Type	Not rated (open device)
Product certifications	NEMA CSA UL Listed

Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901439752
Package weight(Lbs)	4.83 lb(US) (2.19 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------