



## Main

Range	9422T
Product	Disconnect Switch
Disconnect Type	Fusible disconnect switch

## Complementary

Mounting Type	Flange rod variable depth
Current Rating	30 A
Horsepower Rating	7.5 Hp 200 V AC 7.5 Hp 230 V AC 15 Hp 460 V AC 20 Hp 575 V AC 5 hp 250 V DC
Fuse Rating	60 A 250 V 30 A 600 V
Handle Type	6 in handle included NEMA 4/4X enclosures stainless steel
Fuse Type	H J K R

## Environment

Certifications	CSA UL Recognized
----------------	----------------------




## Ordering and shipping details

Category	21732 - 9422
Discount Schedule	CP1
GTIN	00785901316428
Nbr. of units in pkg.	1
Package weight(Lbs)	8.92 lb(US) (4.05 kg)
Returnability	No
Country of origin	MX

## Packing Units

Package 1 Height	6.90 in (17.526 cm)
Package 1 width	11.30 in (28.702 cm)
Package 1 Length	16.00 in (40.640 cm)

Offer Sustainability

EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------