Product data sheet Characteristics

8538SCA11S8V02S

NEMA Combination Starter, Type S, nonfusible disconnect, Size 1, 27A, 10 HP at 600 VAC polyphase, 120 VAC coil, NEMA 12

Main

Contactor application	Non-reversing
Device short name	S

Complementary

Maximum Depth	8.34 in (211.84 mm)	
Device mounting	Surface	
Maximum Height	24 in (609.60 mm)	
NEMA size	1	
Number of poles	3	
Number of thermal units required	3	
Net Weight	40 lb(US) (18.14 kg)	
Reset	Without external	
Maximum Width	9.5 in (241.30 mm)	

Environment

NEMA degree of protection	NEMA 12
Product certifications	CSA LR584 class 3211 04 UL listed file E152395 CCN NKJH7

Ordering and shipping details

Category	21213 - 8538,39 SC,SD(NOT S*R,T,W)	
Discount Schedule	CP1	
Nbr. of units in pkg.	1	
Package weight(Lbs)	50 lb(US) (22.68 kg)	
Returnability	No	
Country of origin	MX	

Offer Sustainability

EU RoHS Directive	Not compliant

Contractual warranty

Warranty 18 months	· · · · · · · · · · · · · · · · · · ·		
•	Warranty	18 months	