

Main

| | |
|---------------------------|--------------------------|
| Product or component type | Starter |
| Type | S |
| Control Circuit Type | Separate control circuit |

Complementary

| | |
|-------------------------|--|
| Control Circuit Voltage | 24 V AC 60 Hz |
| Motor starter type | Non reversing |
| Current Rating | 27 A |
| Number of Poles | 4P |
| Number of Phases | 2 phases |
| Horsepower Rating | 7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC |
| Maximum Voltage Rating | 600 V AC |
| Control Units | No control units |
| Thermal overload type | Melting alloy 2 |
| Electrical connection | Screw clamp terminals |
| NEMA size | 1 |
| Maximum Height | 6.77 in (172 mm) |
| Maximum Depth | 4.21 in (107 mm) |
| Maximum Width | 4.53 in (115 mm) |


Environment

| | |
|------------------------|--------------------------|
| Enclosure Type | Not rated (open device) |
| Product certifications | CSA NEMA UL Listed |

Ordering and shipping details

| | |
|---------------------|------------------------------------|
| Category | 21192 - 8502,36 SC,SD(NOT S*R,T,W) |
| Discount Schedule | CP1 |
| GTIN | 00785901662334 |
| Package weight(Lbs) | 5 lb(US) (2.27 kg) |
| Returnability | No |
| Country of origin | MX |

Offer Sustainability

| | |
|-------------------|---|
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Will be compliant – Date to be confirmed |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|