



### Main

|                           |                        |
|---------------------------|------------------------|
| Product or component type | Starter                |
| Type                      | S                      |
| Control Circuit Type      | Common control circuit |

### Complementary

|                         |                                                                  |
|-------------------------|------------------------------------------------------------------|
| Control Circuit Voltage | 220 V AC 50 Hz<br>240 V AC 60 Hz                                 |
| Motor starter type      | Non reversing                                                    |
| Current Rating          | 18 A                                                             |
| Number of Poles         | 3P                                                               |
| Number of Phases        | 3 phase                                                          |
| Horsepower Rating       | 3 HP 200 V AC<br>3 HP 230 V AC<br>5 HP 460 V AC<br>5 HP 575 V AC |
| Maximum Voltage Rating  | 600 V AC                                                         |
| Control Units           | 2 momentary push-buttons (START-STOP)                            |
| Thermal overload type   | Melting alloy 3                                                  |
| Electrical connection   | Screw clamp terminals                                            |
| NEMA size               | 0                                                                |
| Maximum Height          | 17.24 in (438 mm)                                                |
| Maximum Depth           | 10.98 in (279 mm)                                                |
| Maximum Width           | 14.25 in (362 mm)                                                |

### Environment

|                        |                                |
|------------------------|--------------------------------|
| Enclosure Type         | NEMA 7/9 cast aluminium bolted |
| Product certifications | NEMA                           |

### Ordering and shipping details

|                     |                             |
|---------------------|-----------------------------|
| Category            | 21202 - 8502,36 S*R,S*T,S*W |
| Discount Schedule   | CP1                         |
| Package weight(Lbs) | 50 lb(US) (22.68 kg)        |
| Returnability       | No                          |
| Country of origin   | MX                          |

### Offer Sustainability

|                       |                                                                                                            |
|-----------------------|------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive     | Not compliant                                                                                              |
| China RoHS Regulation |  China RoHS Declaration |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended to be used as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|