



Main

Range of product	Harmony iPC
Product or component type	Power supply module
Accessory / separate part category	Electrical accessory

Complementary

Accessory / separate part destination	HMIBM modular box PC HMIDAD modular display adaptor
Input voltage	100...240 V AC 47...63 Hz
Output voltage	24 V DC
Line Rated Current	4.6 A
Associated fuse rating	3.15 A
Net Weight	1.76 lb(US) (0.8 kg)

Environment

Ambient air temperature for operation	32...122 °F (0...50 °C)
Product certifications	CULus CSA 60950 ATEX UL 60950 CULus HazLoc Class I Division 2 CSA 22-2 No 213 CE CULus HazLoc Class I Division 2 ANSI/ISA 12-12-01 IEC Ex hazardous locations 3GD zone 2/22

Ordering and shipping details

Category	22575 - MAGELIS MC3
Discount Schedule	MC3
GTIN	00785901719366
Nbr. of units in pkg.	1
Package weight(Lbs)	2.6 lb(US) (1.18 kg)
Returnability	No
Country of origin	TW

Packing Units

Package 1 Height	1.57 in (40.000 mm)
Package 1 width	3.94 in (100.000 mm)
Package 1 Length	8.15 in (207.000 mm)

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.