



### Main

Product or component type	Circuit breaker
Trip Unit Type	Thermal-magnetic
Rating Code	Q4

### Complementary

Line Rated Current	400 A
Number of Poles	2P
Interrupt Rating	25 KA 120 V AC 25 kA 240 V AC
[Ue] rated operational voltage	240 V AC
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
Wire Gauge	AWG 1...600 kcmil aluminium/copper)1 AWG 1...250 kcmil aluminium/copper)2
Terminal Type	AL400LA
Magnetic hold current	2000 A
Magnetic tripping current	4000 A
Maximum Height	11 in (279.40 mm)
Maximum Width	6 in (152.40 mm)
Maximum Depth	5.84 in (148.34 mm)
Tightening torque	371.73 Lbf.in (42 N.m) 0.08...0.47 in <sup>2</sup> (50...300 mm <sup>2</sup> ) AWG 1...600 kcmil) 371.73 lbf.in (42 N.m) 0.08...0.19 in <sup>2</sup> (50...120 mm <sup>2</sup> ) AWG 1...250 kcmil)

### Environment

Product certifications	UL Listed IEC CSA
Ambient air temperature for operation	104 °F (40 °C)

### Ordering and shipping details

Category	00933 - Q4L BREAKER & SWITCH
Discount Schedule	DE2
GTIN	00785901649243
Package weight(Lbs)	14.4 lb(US) (6.53 kg)
Returnability	Yes
Country of origin	MX

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause Birth Defects or other reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
EU RoHS Directive	Not applicable, out of EU RoHS legal scope

## Contractual warranty

Warranty	18 months
----------	-----------