

### Main

|                               |                                                                                                                                                                            |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product              | Harmony XB4                                                                                                                                                                |
| Product or component type     | Complete body/contact assembly and light block                                                                                                                             |
| Device short name             | ZB4                                                                                                                                                                        |
| Fixing collar material        | Zamak                                                                                                                                                                      |
| Sale per indivisible quantity | 100                                                                                                                                                                        |
| Contacts type and composition | 1 NO + 1 NC                                                                                                                                                                |
| Contact operation             | Slow-break                                                                                                                                                                 |
| Connections - terminals       | Screw clamp terminals, $\leq 2 \times 1.5 \text{ mm}^2$ with cable end EN 60947-1<br>Screw clamp terminals, $\geq 1 \times 0.22 \text{ mm}^2$ without cable end EN 60947-1 |
| Light source                  | Bulb not included                                                                                                                                                          |
| Bulb base                     | BA 9s                                                                                                                                                                      |
| Light block supply            | Direct $< 2.4 \text{ W}$                                                                                                                                                   |
| [Us] rated supply voltage     | $\leq 250 \text{ V}$                                                                                                                                                       |

### Complementary

|                                             |                                                                                                                                                                                                                                                                          |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAD overall width                           | 1.18 in (30 mm)                                                                                                                                                                                                                                                          |
| CAD overall height                          | 1.85 in (47 mm)                                                                                                                                                                                                                                                          |
| CAD overall depth                           | 1.46 in (37 mm)                                                                                                                                                                                                                                                          |
| Terminals description ISO n°1               | (11-12)NC                                                                                                                                                                                                                                                                |
| Contacts usage                              | Standard                                                                                                                                                                                                                                                                 |
| Positive opening                            | With EN/IEC 60947-5-1 appendix K                                                                                                                                                                                                                                         |
| Operating travel                            | 0.06 in (1.5 mm) NC changing electrical state)<br>0.10 in (2.6 mm) NO changing electrical state)<br>0.17 in (4.3 mm) total travel)                                                                                                                                       |
| Operating force                             | 2 N NC changing electrical state<br>2.3 N NO changing electrical state                                                                                                                                                                                                   |
| Operating torque                            | 0.44 lbf.in (0.05 N.m) NO changing electrical state                                                                                                                                                                                                                      |
| Mechanical durability                       | 5000000 cycles                                                                                                                                                                                                                                                           |
| Tightening torque                           | 7.08...10.62 lbf.in (0.8...1.2 N.m) EN 60947-1                                                                                                                                                                                                                           |
| Shape of screw head                         | Cross Philips no 1<br>Cross pozidriv No 1<br>Slotted flat Ø 4 mm<br>Slotted flat Ø 5.5 mm                                                                                                                                                                                |
| Contacts material                           | Silver alloy (Ag/Ni)                                                                                                                                                                                                                                                     |
| Short-circuit protection                    | 10 A cartridge fuse gG EN/IEC 60947-5-1                                                                                                                                                                                                                                  |
| [Ith] conventional free air thermal current | 10 A EN/IEC 60947-5-1                                                                                                                                                                                                                                                    |
| [Ui] rated insulation voltage               | 600 V 3)EN 60947-1                                                                                                                                                                                                                                                       |
| [Uimp] rated impulse withstand voltage      | 6 kV EN 60947-1                                                                                                                                                                                                                                                          |
| [Ie] rated operational current              | 3 A 240 V, AC-15, A600 EN/IEC 60947-5-1<br>6 A 120 V, AC-15, A600 EN/IEC 60947-5-1<br>0.1 A 600 V, DC-13, Q600 EN/IEC 60947-5-1<br>0.27 A 250 V, DC-13, Q600 EN/IEC 60947-5-1<br>0.55 A 125 V, DC-13, Q600 EN/IEC 60947-5-1<br>1.2 A 600 V, AC-15, A600 EN/IEC 60947-5-1 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                        |                                                                                                                                                                                                                                                                                                                                                                                                           |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electrical durability  | 1000000 Cycles, AC-15, 2 A 230 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C<br>1000000 Cycles, AC-15, 3 A 120 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C<br>1000000 Cycles, AC-15, 4 A 24 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C<br>1000000 Cycles, DC-13, 0.2 A 110 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C<br>1000000 cycles, DC-13, 0.5 A 24 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C |
| Electrical reliability | $\Lambda < 10\exp(-6)$ 5 V 1 mA in clean environment EN/IEC 60947-5-4<br>$\Lambda < 10\exp(-8)$ 17 V 5 mA in clean environment EN/IEC 60947-5-4                                                                                                                                                                                                                                                           |
| Signalling type        | Steady                                                                                                                                                                                                                                                                                                                                                                                                    |

## Environment

|                                       |                                                                                                                                         |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Protective treatment                  | TH                                                                                                                                      |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)                                                                                                              |
| Ambient air temperature for operation | -40...158 °F (-40...70 °C)                                                                                                              |
| Electrical shock protection class     | Class I IEC 60536                                                                                                                       |
| Standards                             | EN/IEC 60947-5-5<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-1<br>UL 508<br>EN/IEC 60947-1<br>JIS C8201-5-1<br>CSA C22.2 No 14<br>JIS C8201-1 |
| Product certifications                | RINA<br>LROS (Lloyds register of shipping)<br>BV<br>DNV<br>GL<br>CSA<br>UL Listed                                                       |
| Vibration resistance                  | 5 gn 2...500 Hz)IEC 60068-2-6                                                                                                           |
| Shock resistance                      | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>50 gn 11 ms) half sine wave acceleration IEC 60068-2-27                      |

## Ordering and shipping details

|                     |                        |
|---------------------|------------------------|
| GTIN                | 03389110882162         |
| Package weight(Lbs) | 0.00 lb(US) (0.001 kg) |

## Packing Units

|                  |          |
|------------------|----------|
| Package 1 Height | 0.560 dm |
| Package 1 width  | 0.340 dm |
| Package 1 Length | 0.540 dm |


## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---

Dimensions

---



Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

| Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board                                                                                                                                                                                                                                                                                                                                                        | Connection by Faston Connectors |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
|                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                 |
| <div> <div>(1)</div> <div>Diameter on finished panel or support</div> <div>(2)</div> <div>40 mm min. / 1.57 in. min.</div> <div>(3)</div> <div>30 mm min. / 1.18 in. min.</div> <div>(4)</div> <div>Ø 22.5 mm / 0.89 in. recommended (Ø 22.3 mm <sub>0</sub><sup>+0.4</sup> / 0.88 in. <sub>0</sub><sup>+0.016</sup>)</div> <div>(5)</div> <div>45 mm min. / 1.78 in. min.</div> <div>(6)</div> <div>32 mm min. / 1.26 in. min.</div> </div> |                                 |