

15S4FSS

TRANSFORMER DRY 1 PHASE 15 KVA 120/240V SECONDARY

Main

Product or component type	Dry Sealed Transformer
Primary Voltage	600 V
Full Capacity Taps	2 5 % FCBN
Secondary Voltage	120/240 V

Complementary

Enclosure Code	15B
Phase	1 phase
Primary to Secondary Voltage	600 V 120/240 V
Power Rating	15 kVA
Temperature rise	115 °C
Maximum Height	20 in (508.00 mm)
Maximum Width	15 in (381.00 mm)
Maximum Depth	13.5 in (342.90 mm)
Enclosure mounting	Wall mounted
Enclosure material	Stainless steel

Environment

Enclosure Type	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product certifications	CULus UL Listed CSA

Ordering and shipping details

Package weight(Lbs)	0.16 oz (4.536 g)
---------------------	-------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.