



Main

Product or component type	Starter
Type	S
Control Circuit Type	Control circuit transformer

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	540 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	150 HP 200 V AC 200 HP 230 V AC 400 HP 460 V AC 400 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Auxiliary Contacts	2 NO + 2 NC
Control Circuit Fusing	2 fuses (primary), 2 fuses (secondary)
Thermal overload type	Melting alloy 3
Electrical connection	Screw clamp terminals
NEMA size	6
Maximum Height	28.07 in (713 mm)
Maximum Depth	9.96 in (253 mm)
Maximum Width	10.55 in (268 mm)

Environment

Enclosure Type	Not rated (open device)
Product certifications	UL Listed NEMA CSA

Ordering and shipping details

Category	21195 - 8502,36 SH,SJ(NOT S*R,T,W)
Discount Schedule	CP1
Package weight(Lbs)	110 lb(US) (49.90 kg)
Returnability	Yes
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Not compliant
-------------------	---------------

Contractual warranty

Warranty	18 months
----------	-----------