



### Main

Product or component type	Industrial Control Transformer
Power Rating	250 VA
Primary Voltage	208/230/460 V
Secondary Voltage	115 V
Type	T

### Complementary

Number of Phases	1 phase
Power Rating	250 VA UL 250 VA CSA 250 VA NOM 160 VA
Primary to Secondary Voltage	208/230/460 V 115 V
Temperature rise	80 °C
Electrical connection	Screw clamp terminals
Maximum Height	3.84 in (97.54 mm)
Maximum Width	4.5 in (114.30 mm)
Maximum Depth	4.74 in (120.40 mm)
Material	Copper winding
Fingersafe Cover Compatibility	FSC2

### Environment

Product certifications	CSA file LR37055 guide 184-N-90 UL listed file E61239
Enclosure Type	Not rated (open device)
Insulation temperature	266 °F (130 °C)

### Ordering and shipping details

Category	16201 - 9070 T (NOT TF) 250-2000VA
Discount Schedule	CP8
GTIN	00785901905127
Nbr. of units in pkg.	1
Package weight(Lbs)	9.21 lb(US) (4.18 kg)
Returnability	Yes
Country of origin	MX

### Packing Units

Package 1 Height	6.50 in (16.510 cm)
Package 1 width	6.80 in (17.272 cm)
Package 1 Length	7.70 in (19.558 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	10 Years
----------	----------