

### Main

Device short name	FHG
Enclosure type	Standard environment enclosure indoor
Factory modification	Maintained manual cut-in lever (AUTO-ON) Quick connect two-way pressure release valve (for use with polyflow tubing)
Product specific application	Control small electrically driven air compressors
Quantity per set	Set of 16
Range of product	Square D Pumptrol
Type of packing	Bulk

### Complementary

Adjustable range on rising pressure	100...200 psi (689.48...1378.95 kPa)
Approximate fixed differential	35 psi (241.32 kPa)
Contact code designation	A600
Maximum Depth	2.78 in (70.61 mm)
Electrical connection	Screw clamp terminal
Fixing mode	By brackets
Fluid connection type	0.25 inch 4-way flange
Maximum Height	2.8 in (71.12 mm)
Materials in contact with fluid	Nitrile (Buna-N) diaphragm
Maximum pressure	220 psig
Maximum Horse Power Rating	1 Hp 460/575 V AC, 3 phase 2 Hp 115 V AC, 1 phase 3 Hp 115 V AC, 3 phase 3 Hp 230 V AC, 1 phase 5 hp 230 V AC, 3 phase
Number of poles	2
Permissible voltage	575 V AC
Pressure actuator	Diaphragm
Pressure setting range	965.27 kPa (140 psi) off
Net Weight	1.13 lb(US) (0.51 kg)
Scale type	Fixed differential
Switch function	DPST
Maximum Width	3.76 in (95.50 mm)

### Environment

NEMA degree of protection	NEMA 1
Product certifications	UL listed file E12158 CCN NKPZ CSA LR25490 class 3211 06

### Ordering and shipping details

Category	21533 - 9013 FHG (INDIVIDUAL-DISCOUNT CP7I)
Discount Schedule	CP7I
GTIN	00785901607465
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

Contractual warranty

Warranty	18 months
----------	-----------