

# 8903LXG80V81FF4T

8903LX mechanically held lighting contactor, 8 P, 8 NO, 30 A, 600 V, 480/120 V 60 Hz, NEMA 1



## Main

Product or component type	Mechanically Held Lighting Contactor
Range of product	8903LX
Control Circuit	Control circuit transformer

## Complementary

Control Voltage	480 V AC 60 Hz primary circuit 120 V AC 60 Hz secondary circuit
Inrush power in VA	180 VA 60 Hz 25 VA 50/60 Hz
Current Rating	20 A tungsten 30 A fluorescent
Number of Poles	8P 8 NO
Control Unit	No control units
Pilot Light	No indicator
Control Circuit Fusing	2 fuses primary circuit 1 fuse secondary circuit
Other Options	None
Electrical connection	Screw-clamp terminals
Maximum Height	11.89 in (302 mm)
Maximum Depth	7.44 in (189 mm)
Maximum Width	11.89 in (302 mm)






## Environment

Enclosure Type	NEMA 1 painted sheet steel surface
Product certifications	UL Listed CSA

## Ordering and shipping details

Category	21322 - 8903 LX (NOT L)
Discount Schedule	CP1
Package weight(Lbs)	57.5 lb(US) (26.08 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>

Contractual warranty

Warranty	18 months
----------	-----------