Product data sheet Characteristics

8903SMC64V03

Contactor, NIGHT MASTER, combination lighting, 30A, 3 pole, fuse, 220/240 VAC 50/60 Hz coil. NEMA 3R

Main

| Type | Night-Master | |
|------|--------------|--|
|------|--------------|--|

Complementary

| Control Circuit Voltage | 240 V AC 60 Hz | |
|-------------------------|---------------------|--|
| | 220 V AC 50 Hz | |
| Current Rating | 30 A | |
| Number of Poles | 3P | |
| Control Units | No control units | |
| Pilot Light | Without pilot light | |
| Auxiliary Contacts | Without | |
| Other Options | None | |
| Electrical connection | Lugs | |
| Maximum Height | 38.86 in (987 mm) | |
| Maximum Depth | 10.43 in (265 mm) | |
| Maximum Width | 15.00 in (381 mm) | |
| | | |

Environment

| Enclosure Type | NEMA 3R painted sheet steel surface none |
|------------------------|--|
| Product certifications | UL listed file E16151 CCN NRNT |

Ordering and shipping details

| Category | 21326 - 8903 S*C |
|---------------------|-----------------------|
| Discount Schedule | CP1 |
| Package weight(Lbs) | 105 lb(US) (47.63 kg) |
| Returnability | No |
| Country of origin | MX |

Offer Sustainability

| EU RoHS Directive | Will be compliant – Date to be confirmed |
|-------------------|--|
| | |

Contractual warranty

| · · · · · · · · · · · · · · · · · · · | | |
|---------------------------------------|-----------|--|
| Warranty | 18 months | |