HMIYPSPMAC1

AC / DC power adapter for Harmony iPC



Main

Range of product	Harmony iPC
Product or component type	External power supply module
Accessory / separate part category	Adaptation accessory

Complementary

HMIBM modular box PC HMIDAD modular display adaptor	
110240 V AC 4763 Hz	
24 V DC	
6.25 A	
Harmony iPC	
7.44 in (189 mm)	
3.52 in (89.5 mm)	
1.79 in (45.5 mm)	
	HMIDAD modular display adaptor 110240 V AC 4763 Hz 24 V DC 6.25 A Harmony iPC 7.44 in (189 mm) 3.52 in (89.5 mm)

Environment

Ambient air temperature for operation	32158 °F (070 °C)
Ambient air temperature for storage	-40185 °F (-4085 °C)
Relative humidity	095 % non-condensing
Product certifications	CE UL 60950 CULus CSA 60950

Ordering and shipping details

Category	22575 - MAGELIS MC3
Discount Schedule	MC3
GTIN	00785901711865
Nbr. of units in pkg.	1
Package weight(Lbs)	3.3 lb(US) (1.50 kg)
Returnability	No
Country of origin	TW

Packing Units

Package 1 Height	5.91 in (150.000 mm)
=	
Package 1 width	9.06 in (230.000 mm)
Package 1 Length	14.57 in (370.000 mm)
	,

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.