Product data sheet Characteristics

ZBVJ65

blue light block for head Ø22 integral LED 12V spring clamp terminals





Main

Range of product	Harmony XB5 Harmony XB4
Product or component type	Light block
Device short name	ZBV
Sale per indivisible quantity	4
Connections - terminals	Spring clamp terminals
Signalling type	Steady
Light source	Protected LED
Bulb base	Integral LED
Light block supply	Direct
Light source colour	Blue
[Us] rated supply voltage	12 V AC/DC 50/60 Hz

Complementary

Net Weight	0.04 lb(US) (0.017 kg)	
Supply voltage limits	1015 V DC 10.213.8 V AC	
Current consumption	18 mA	
Service life	100000 h at rated voltage and 25 °C	
Surge withstand	1 kV IEC 61000-4-5	
Mounting of block	Front mounting	
Electrical composition code	M1 M2 M3 M4 M5 M6 M10 MF1 P1 P2 PF1	

Environment

Protective treatment	TH	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-40158 °F (-4070 °C)	
IP degree of protection	IP20 IEC 60529	
Standards	EN/IEC 60947-5-4 EN/IEC 60947-5-5 UL 508 CSA C22.2 No 14 EN/IEC 60947-1 EN/IEC 60947-5-1 JIS C8201-5-1 JIS C8201-1	
Resistance to fast transients	2 kV IEC 61000-4-4	
Resistance to electromagnetic fields	9.14 V/m (10 V/m) IEC 61000-4-3	

Resistance to electrostatic discharge	6 KV on contact (on metal parts) IEC 61000-4-2 8 kV in free air (in insulating parts) IEC 61000-4-2
Electromagnetic emission	Class B IEC 55011
Ordering and chinning details	
Ordering and shipping details Category	22469 - PUSHBUTTON,22MM ACCESSORIES-NEW
Discount Schedule	CS2
GTIN	00785901813026
Nbr. of units in pkg.	4
Package weight(Lbs)	0.5 lb(US) (0.23 kg)
Returnability	No No
Country of origin	FR
Packing Units	
Package 1 Height	0.560 dm
Package 1 width	0.440 dm
Package 1 Length	0.540 dm
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Environmental Disclosure Circularity Profile	End Of Life Information

Contractual warranty


Contractad Warranty	
Warranty	18 months

Product data sheet Dimensions Drawings

ZBVJ65

Dimensions

with ZB5AZ009 Fixing Collar



with ZB4BZ009 Fixing Collar

