Product data sheet Characteristics

9080FB3631C

Terminal Block Class H Fuseholder 3 Pole 600V 100A Copper Lug



Main		
Range	9080FB	
Product	Fuse holder	

Complementary

Current Rating	100 A
[Ue] rated operational voltage	<= 600 V AC/DC
Fuse type	Н
Fuse size	1 x 7.875 in
Number of poles	3
Electrical connection	Box lugs
Wire Gauge	AWG 6AWG 2/0 copper or aluminium
SCCR	10 kA UL 512
Product certifications	CSA file 70360 class 6225 01 CE
	UL listed file E40747 CCN IZLT
Operating Temperature	-40302 °F (-40150 °C)
Mounting Type	Surface mount
Block Material	Phenolic block
Wire stripping length	1.3125 in (33.34 mm)
Terminal Tightening Torque	Lugs 4.52 N.m (40 lbf.in) AWG 8 copper or aluminium Lugs 3.95 N.m (35 lbf.in) AWG 14 copper Lugs 13.56 N.m (120 lbf.in) AWG 6AWG 2/0 copper or aluminium Lugs 3.95 N.m (35 lbf.in) AWG 12AWG 10 copper or aluminium
Maximum Height	8.12 in (206.25 mm)
Maximum Width	5.73 in (145.54 mm)
Maximum Depth	2.6 in (66.04 mm)

Ordering and shipping details

Category	21701 - 9080 FB	
Discount Schedule	CP1	
GTIN	00785901097167	
Package weight(Lbs)	2.98 lb(US) (1.35 kg)	
Returnability	No	
Country of origin	US	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☐ China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------