



Main

Product	Buck and Boost Transformer
Enclosure Code	8A
Enclosure Type	NEMA 3R
Insulation Temperature	356 °F (180 °C)
Primary Voltage	120 x 240 V
Power Rating	1.5 kVA
Secondary Voltage	16/32 V
Temperature Rise	115 °C

Ordering and shipping details

16265 - BUCK & BOOST	
PE2	
00785901876458	
38.24 lb(US) (17.35 kg)	
Yes	
MX	
	PE2 00785901876458 38.24 lb(US) (17.35 kg) Yes

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Contractical Warranty		
Warranty	18 months	