



Main

Device short name	EGX300
Product or component type	Gateway module
Device application	Gateway Server
Range compatibility	Masterpact Compact PowerPact

Complementary

Communication network type	RS232/485, Modbus RTU and ASCII even/odd or none 38400/57600 bauds SUB-D 9 RS232/485, PowerLogic (SY/MAX) even/odd or none 38400/57600 bauds SUB-D 9 RS232/485, JBUS even/odd or none 38400/57600 bauds SUB-D 9 Ethernet, HTTP RJ45 Ethernet, Modbus TCP/IP RJ45 Ethernet, FTP RJ45 Ethernet, SNMP RJ45 Ethernet, BOOTP (Bootstrap Protocol) RJ45
Communication gateway	Ethernet/fieldbus
Web server	Embedded
Mounting mode	By clips
Mounting support	35 mm DIN rail
Control type	By software
[Us] rated supply voltage	24 V DC
Power consumption in W	4 W
Product certifications	UL 508 FCC Class A CUL
Standards	EN 61000-4-2 EN 61000-4-5 EN 61000-6-2 UL 60950 EN 61000-4-3 EN 61000-4-8 EN/IEC 60950 EN 61000-4-6 EN 55011 EN 55022 EN 61000-4-4
Maximum Height	3.18 in (80.8 mm)
Maximum Width	2.83 in (72 mm)
Maximum Depth	2.59 in (65.8 mm)
Net Weight	0.37 lb(US) (0.17 kg)
Language	English Italian Spanish Chinese German French

Environment

IP degree of protection	IP30
Relative humidity	5...95 % 131 °F (55 °C) without condensation
Ambient air temperature for operation	-13...158 °F (-25...70 °C)

Ordering and shipping details

Category	09785 - POWERLOGIC SYSTEM CMPNTS
Discount Schedule	PL1
GTIN	00785901673262
Nbr. of units in pkg.	1
Package weight(Lbs)	0.74 lb(US) (0.34 kg)
Returnability	No
Country of origin	IN

Packing Units

Package 1 Height	4.92 in (12.500 cm)
Package 1 width	4.53 in (11.500 cm)
Package 1 Length	4.92 in (12.500 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------