

## Product data sheet

### Characteristics

# MPR64200

MP Meter Pak, meter center, four ringless sockets, no bypass, 5th jaw, OH, UG, 600 A bus, 200 A, 240 VAC single phase 3W



### Main

Product	Meter Center
Socket Rating	200 A
Main Type	Main Lugs
Number of Jaws	5
Number of Meter Sockets	4
Socket Type	Ringless

### Complementary

Main Rating	600 A 400 A
Bus Rating	600 A
Certifications	UL Listed
Type	Meter-Pak
Busbar Material	Aluminium busbar
Bypass Type	No bypass
Enclosure Material	Steel
Enclosure Rating	NEMA 3R
Maximum Voltage Rating	240 V AC
Mounting	Surface
Phase	1 phase
Service Feed Location	OH UG
Wire Size	AWG 1/0...600 kcmil 1 aluminium AWG 1/0...600 kcmil 1 copper
Wire Configuration	3-wire
Maximum Height	52.00 in (1320.80 mm)
Maximum Width	747.78 mm (29.44 in)
Maximum Depth	210.31 mm (8.28 in)

### Ordering and shipping details

Category	00021 - METER-PAK
Discount Schedule	DE4
GTIN	00785901410478
Package weight(Lbs)	115 lb(US) (52.16 kg)
Returnability	Yes
Country of origin	MX

### Offer Sustainability

EU RoHS Directive	Will be compliant – Date to be confirmed
-------------------	--

### Contractual warranty

Warranty	18 months
----------	-----------