



Main

Product	Surge protection device
Range	Square D
Device Short Name	HEPD
Type of packing	Wholesale

Complementary

Surge Current	80 kA per phase
Voltage Rating	120/240 V AC
Number of Phases	1 phase
Wiring Configuration	3-wire (isolated ground)
MCOV	150 V
Rated Current	10 kA
SCCR	25 kA
Local Signalling	1 LED green normal operation
Input voltage	600 V L - N 600 V L - G 1000 V L - L 900 V N - G
Height	3.23 in (82.04 mm)
Width	3.72 in (94.49 mm)
Depth	2.10 in (53.34 mm)

Environment

Enclosure Rating	NEMA 4X
Standards	CSA C22.2 No 8 UL 1449 CUL UL 1449:ed. 4 type II
Ambient Operating	-31...149 °F (-35...65 °C)

Ordering and shipping details

Category	08461 - SURGE PROTECTION RESI
Discount Schedule	DE1B
GTIN	00785901139911
Package weight(Lbs)	1.4 lb(US) (0.64 kg)
Returnability	Yes
Country of origin	US

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Approximate Dimensions

