

### Main

Range of product	8501X
Relay type	Control relay
Product or component type	Latching device

### Complementary

[Uc] control circuit voltage	90 V DC
Coil Voltage Limits	Operational 0.8...1.1 Uc DC
Inrush Power in Watts	18 W
Sealed Power in Watts	18 W
Electrical connection	Screw clamp terminals
Wire Gauge	AWG 18...AWG 12 copper
Terminal Tightening Torque	Control circuit 9.03...12.04 lbf.in (1.02...1.36 N.m) screw terminals

### Environment

Product certifications	CE CSA LR60905 class 3211 02 UL recognized E78403 CCN NKCR2
------------------------	---

### Ordering and shipping details

Category	21159 - 8501 X ACCESSORIES
Discount Schedule	CP2
Package weight(Lbs)	0.4 lb(US) (0.18 kg)
Returnability	No

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

Contractual warranty

Warranty	18 months
----------	-----------