

Main

Range of product	Harmony XVR
Product or component type	Prewired rotating mirror beacon
Sound signalling	Without
Device short name	XVR
Mounting diameter	5.12 in (130 mm)
IP degree of protection	IP66 IEC 60529 IP67 IEC 60529
[Us] rated supply voltage	230 V AC
Light source	High luminosity LED, red

Complementary

Material	ABS (acrylonitrile butadiene-styrene) body part PC globe	
CAD overall width	5.12 in (130 mm)	
CAD overall depth	5.12 in (130 mm)	
Net Weight	2.18 lb(US) (0.99 kg)	
Marking	CE	
Product mounting	By 3 M6 screws	
[Uimp] rated impulse withstand voltage	4 kV	
Current consumption	22 mA	
Flashing frequency	2.7 Hz	
Clamping connection capacity	1.25 mm²	
AWG gauge	AWG 18	
Cable length	15.75 in (400 mm)	

Environment

Standards	EN/IEC 60947-5-1 EN/IEC 60947-1	
Protective treatment	TC	
Ambient air temperature for storage	-31158 °F (-3570 °C)	
Ambient air temperature for operation	-22122 °F (-3050 °C)	
Electrical shock protection class	Class II IEC 61140	

Ordering and shipping details

Category	22617 - XVC TOWER LIGHTS	
Discount Schedule	XV	
GTIN	00785901944843	
Nbr. of units in pkg.	1	
Package weight(Lbs)	2.97 lb(US) (1.35 kg)	
Returnability	No	
Country of origin	ID	

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.48 in (19 cm)
Package 1 width	7.48 in (19 cm)
Package 1 Length	10.83 in (27.5 cm)
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Weight	20.61 lb(US) (9.35 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	15.75 in (40 cm)
Package 2 Length	23.62 in (60 cm)
Unit Type of Package 3	P06
Number of Units in Package 3	24
Package 3 Weight	100.47 lb(US) (45.572 kg)
Package 3 Height	30.31 in (77 cm)
Package 3 width	31.50 in (80 cm)
Package 3 Length	23.62 in (60 cm)

Offer Sustainability

WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Yes
₫Yes
☐ China RoHS Declaration
Product Environmental Profile
☐ End Of Life Information

Contractual warranty


Warranty	18 months
----------	-----------


Product data sheet Dimensions Drawings

XVR13M04L

Rotating Mirror Beacon

Dimensions





Product data sheet Mounting and Clearance

XVR13M04L

Rotating Mirror Beacon

Panel Cut-out

