



Main

Range	TeSys
Product or component type	Coil
Range compatibility	TeSys Integral contactor breaker
Device short name	LX1
Control circuit type	AC 50/60 Hz
[Uc] control circuit voltage	380...400 V AC 50 Hz 460...480 V AC 60 Hz
Average resistance	93.63 Ohm 68 °F (20 °C)
Inductance of closed circuit	20 H

Complementary

Control circuit voltage limits	Operational 0.85...1.1 Uc 131 °F (55 °C)) Drop-out 0.25...0.7 Uc 131 °F (55 °C))
Inrush power in VA	420...500 VA 60 Hz 0.55 350...400 VA 50 Hz 0.55
Hold-in power consumption in VA	24...36 VA 60 Hz 0.28 20...30 VA 50 Hz 0.28

Environment

Net Weight	0.66 lb(US) (0.3 kg)
------------	----------------------

Ordering and shipping details

Category	22341 - CONTACTOR,D,K,&F ACCESS
Discount Schedule	I12
GTIN	00785901227007
Nbr. of units in pkg.	1
Package weight(Lbs)	0.73 lb(US) (0.33 kg)
Returnability	No
Country of origin	FR

Packing Units

Package 1 Height	0.800 dm
Package 1 width	0.750 dm
Package 1 Length	1.050 dm

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide which is known to the State of California to cause Carcinogen harm. For more information go to www.p65warnings.ca.gov
---------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Contractual warranty

Warranty	18 months
----------	-----------