Product data sheet Characteristics

ZB4BZ1015

single contact block with body/fixing collar 1NO spring clamp terminal





Main

Range of product	Harmony XB4
Product or component type	Complete body/contact assembly
Device short name	ZB4
Fixing collar material	Zamak
Sale per indivisible quantity	1
Head type	Standard
Contacts type and composition	1 NO
Contact operation	Slow-break
Contact block type	Single
Device composition	Fixing collar Body
Connections - terminals	Spring clamp terminals

Complementary

CAD overall width	1.18 in (30 mm)	
CAD overall height	1.85 in (47 mm)	
CAD overall depth	1.46 in (37 mm)	
Terminals description ISO n°1	(13-14)NO	
Net Weight	0.12 lb(US) (0.053 kg)	
Contacts usage	Standard contacts	
Positive opening	Without	
Operating travel	0.10 in (2.6 mm) NO changing electrical state)	
Operating force	2.3 N NO changing electrical state	
Operating torque	0.44 lbf.in (0.05 N.m) NO changing electrical state	
Mechanical durability	5000000 cycles	
Contacts material	Silver alloy (Ag/Ni)	
Electrical durability	10000000 cycles	
Device presentation	Basic sub-assemblies	

Environment

Protective treatment	TH
Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-40158 °F (-4070 °C)
IP degree of protection	IP20 IEC 60529
Standards	EN/IEC 60947-5-4 EN/IEC 60947-1 EN/IEC 60947-5-1 CSA C22.2 No 14 EN/IEC 60947-5-5 UL 508 JIS C8201-5-1 JIS C8201-1

Product certifications	CSA BV	
	GL UL	
	LROS (Lloyds register of shipping)	
	DNV	
	RINA	
Vibration resistance	5 gn 2500 Hz)IEC 60068-2-6	
Shock resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27	

Ordering and shipping details

ordoning and ompping dotaile	
Category	22469 - PUSHBUTTON,22MM ACCESSORIES-NEW
Discount Schedule	CS2
GTIN	00785901833901
Nbr. of units in pkg.	1
Package weight(Lbs)	0.12 lb(US) (0.05 kg)
Returnability	Yes
Country of origin	FR

Packing Units

r acking onits	
Unit Type of Package 1	PCE
Package 1 Height	1.34 in (3.4 cm)
Package 1 width	1.34 in (3.4 cm)
Package 1 Length	2.13 in (5.4 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	9.35 oz (265 g)
Package 2 Height	1.65 in (4.2 cm)
Package 2 width	1.34 in (3.4 cm)
Package 2 Length	10.39 in (26.4 cm)
Unit Type of Package 3	S03
Number of Units in Package 3	200
Package 3 Weight	24.16 lb(US) (10.958 kg)
Package 3 Height	11.81 in (30 cm)
Package 3 width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months