



Main

Product	Double Throw Safety Switch
Current Rating	200 A
Certifications	UL Listed
Enclosure Rating	NEMA 1 steel
Factory Installed Neutral	Neutral (factory installed)
Disconnect Type	Non-fusible disconnect switch
Mounting Type	Surface
Number of Poles	2
Voltage Rating	240 V AC 250 V DC
Wire Size	AWG 6...300 kcmil copper or aluminium

Complementary

Maximum Horse Power Rating	15 hp 240 V AC 1 phase NEC 240.6
Maximum Width	19.63 in (498.60 mm)
Maximum Height	30.88 in (784.35 mm)
Maximum Depth	9.75 in (247.65 mm)
Tightening torque	340 lbf.in (38.41 N.m) AWG 6...300 kcmil)

Ordering and shipping details

Category	00033 - DT SWITCH,NEMA1
Discount Schedule	DE1
GTIN	00785901017417
Nbr. of units in pkg.	1
Package weight(Lbs)	52 lb(US) (23.59 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	10.50 in (26.67 cm)
Package 1 width	17.90 in (45.466 cm)
Package 1 Length	31.80 in (80.772 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------